











Insulated container for the transport of temperaturecontrolled products

Brand: MELFORM

Country of origin: ITALYCustoms code: 39231090

ATP Certificate

Compatible with food contact

Color: grey/blue
 Capacity: 370 liters.
 Technology: rotomoulding
 Warranty: 24 months

• Fully recyclable at the end of its operational life.

MANUFACTURING MATERIALS insulating material between inner and outer walls of container and the walls of the container **Polyethylene Polyurethane** door; suitable for food contact and the door, free of CFC and HCFC Silicone rubber Nylon wheels gasket handling handles, closing **Polypropylene** Hinges Stainless steel handle, internal door rod hinge rods, hinge rod connection **Galvanized steel** plates, wheel support

Model	Code	EAN code	Ext. dim (mm)	Int. dim. (mm)	Capacity (I)	Weight (kg)
CARGO 370 Basic	03709004	8022949106065	800x840xh1185	615x630xh960	370	67,5
Cargo 370 wheels	03700001	8022949102234	800x840xh1310	615x630xh960	370	70
Cargo 370 feet	03700003	8022949108601	800x840xh1310	615x630xh960	370	70
Cargo 370 pallet	03700010	8022949148140	800x840xh1310	615x630xh960	370	83



Overall heat transfer coefficient: K=0.32 W/m²K

Container (isothermal body) granted for use: from -30°C to +100°C.

PRODUCT FEATUR	ES		
	3 housing seats of grids positioned at 335/500/665mm from the bottom of the container.		4 wheels with a diameter of 100 mm (2 fixed and 2 swivel, one of which is equipped with a brake). Wheel support plate integrated in the container.
	Stainless steel closing handle with release button.		Handle prepared for the use of tamper-evident system.
	Stainless steel rod with 2 hooks integrated inside the door.		Door can be opened up to 270° with tongue door.
	Fresh, frozen and frozen plus eutectic plates , to increase thermal maintenance performance over time		Double pin hinges. Improved stability of the door over time.
	Internal grooves to ensure good air circulation.		Right internal temperature thanks to the thermometer inserted in the door (on request)
bengricle*	USB datalogger to record temperature data during transport.	RFID	RFID systems for traceability

ACCESSORIES						
Model	Code	Color	Ext. dim (mm)	Weight (kg)		
Card holder	RRI141		A5			
Stainless steel grid	AEA018		650x610xh16	3,85		
Eutectic plate Fresh +3°C - 2 x Cargo -	PE500001	rose	540x325xh57	6,8		
Eutectic plate Frozen - 21°C - 2 x Cargo -	PE500002	blue	540x325xh57	6,8		
Eutectic plate Frozen plus - 21°C - 2 x Cargo -	PE500908	green	540x325xh57	6,8		
USB Data Logger, Temperature range - 30°C +70°C	AFG007		80x33xh14			
Analog thermometer +40°C- 40°C	RRI165					
Floor/vehicle fixing kit (for basic version)	RRI222					