


ATP


Insulated container for the transport of temperature-controlled products













- Brand: MELFORM
- Country of origin: ITALY
- Customs code: 39231090
- ATP Certificate
- Compatible with food contact
- Color: grey/blue
- Capacity: 500 liters.
- Technology: rotomoulding
- Warranty: 24 months
- Fully recyclable at the end of its operational life.

MANUFACTURING MATERIALS

Polyethylene	inner and outer walls of container and door; suitable for food contact	Polyurethane	insulating material between the walls of the container and the door, free of CFC and HCFC
Silicone rubber	gasket	Nylon	wheels
Galvanized steel	wheel support	Stainless steel	handling handles, closing handle, internal door rod, hinge rod

Model	Code	EAN code	Ext. dim. (mm)	Int. dim. (mm)	Capacity (l)	Weight (Kg)
Cargo 500 Basic	05009039	8022949106041	715x850xh1545	540x660xh1370	500	87,5
Cargo 500 wheel	05000071	8022949104207	715X850Xh1675	540x660xh1370	500	90
Cargo 500 feet	05000081	8022949113230	715X850Xh1675	540x660xh1370	500	90
Cargo 500 pallet	05000074	8022949104160	715X850Xh1675	540x660xh1370	500	105

PRODUCT FEATURES

	4 wheels diameter 100 mm (2 fixed and 2 swivel, one of which with brake). Wheel support plate integrated in the container.		Version with pallet with galvanized steel frame at 4 feet of h 120 mm. or with 4 feet in galvanized steel h 130 mm.
	1 housing seat of the grid positioned 600mm from the bottom of the container.		Fresh, frozen and frozen plus eutectic plates, to increase thermal maintenance performance over time
	Stainless steel closing handle with release button.		Handle prepared for the use of tamper-evident system.
	Stainless steel rod with 2 hooks integrated inside the door.		Openable door up to 270° with latch - tab door.
	Analog thermometer inserted into the door		Tilting plastic grid
	USB datalogger to record temperature data during transport.		RFID systems for traceability
K	Overall heat transfer coefficient: K=0,35 W/m²K	°C	Granted for use: -30°C +100°C.

ACCESSORIES

Model	Code	Color	Ext. dim. (mm)	Weight (Kg)
Card holder	RRI141		A5	
Stainless steel grid	AEA008		550x650xh16	1,8
Tilting plastic grid	PAPE0001	grey	535x594xh20	1,1
Eutectic plate fresh +3°C - 2 x Cargo -	PE500001	rose	540x325xh57	6,8
Eutectic plate frozen – 21°C - 2 x Cargo -	PE500002	blue	540x325xh57	6,8
Eutectic plate Frozen Plus – 21°C - 2 x Cargo -	PE500908	green	540x325xh57	6,8
USB Data Logger -30°C +70°C	AFG007		80x33xh14	
Floor/vehicle container fixing kit (for basic version)	RRI222			
Eutectic plate retainer safety kit	RRI180			
Analog thermometer +40°C- 40°C	RRI165			